


# Polysafe™ Stone fx PUR

Polysafe Stone fx PUR is a heavy-duty safety flooring collection in a range of high clarity stone and concrete effects. Clear aluminium oxide particles which are virtually invisible to the naked eye are integrated throughout the performance layer to provide a safety flooring which is both functional and beautiful. These caborundum-free safety particles ensure that Polysafe Stone fx PUR offers full HSE compliance and sustainable wet slip resistance. For use in heavy commercial and residential installations including education, health and care, social housing, leisure and retail sectors.



	<b>Gauge</b>	EN 428/ISO 24346	2.0mm
	<b>Wear Layer</b>	EN 429/ISO 24340	0.70mm
	<b>Roll Size</b>	EN 426/ISO 24341	2m x 20m = 40m <sup>2</sup>
	<b>Total Weight</b>	EN 430/ISO 23997	2780g/m <sup>2</sup>
	<b>General Performance</b>	EN 13845 ASTM F1303	Conforms Conforms
	<b>Use Area</b>	EN 685/ISO 10874	
	<b>Enhanced Slip Resistance</b>	EN 13845 AS 4586 DIN 51130 RRL Pendulum Test Surface Roughness	ES1 R10 R10 ≥36 (wet test - 4S Rubber/Slider 96) Rz ≥20µm
<p>The wet slip resistance across all Polysafe products is sustainable throughout the guaranteed life of the product, with strict adherence to HSE Guidelines. For further clarification regarding slip resistance, consult Polyflor.</p>			
	<b>Abrasion Resistance</b>	EN 13845	50,000 cycles
	<b>Reaction to Fire</b>	EN 13501-1 ASTM E648 AS ISO 9239-1 CAN/ULC S-102.2	Class Bfl-S1 Class 1 >8.0KW/m <sup>2</sup> FSV < 300; SDV < 500
	<b>Static Electrical Propensity</b>	EN 1815	≤2.0kV Classified as 'antistatic'
	<b>VOC Emissions</b>	AgBB/ABG FloorScore Finnish MI Classification	Very low emissions Certified Certified
	<b>Resistance to Chemicals</b>	EN 423/ISO 26987	Good chemical resistance
<p><b>Agrément Assurance</b> - Polysafe Stone fx PUR has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance, the appearance, colour and slip resistance will be retained during this period.</p>			
<p><b>Environmentally Preferable Flooring</b> - Polysafe Stone fx PUR achieves BRE Global A+ rating (Generic) in the Green Guide to Specification in use areas such as education and healthcare. Generic EN 15804 Environmental Product Declaration (EPD) available on request. It is 100% recyclable and contains 10% recycled material. Recyclable via the Recofloor scheme. Visit <a href="http://www.polyflor.com/sustainability">www.polyflor.com/sustainability</a>.</p>			
<p><b>Polysafe PUR</b> - Polysafe Stone fx PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention. As with all Polysafe products, Polysafe Stone fx PUR should not have a polish applied.</p>			
	<b>Hygiene</b>	<p>All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.</p>	
		<p>Polysafe safety flooring ranges have good resistance to dilute acids and alkalis, are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. Chemical resistance charts available on request. For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email <a href="mailto:tech@polyflor.com">tech@polyflor.com</a>.</p> <p>As with all Polysafe products, Polysafe Stone fx PUR should not have a polish applied. For best results, flooring must be reversed laid. The data presented is correct at the time of printing. For latest information, please visit our website <a href="http://polyflor.com">polyflor.com</a>.</p> <p>Decoration and shade may vary slightly from the samples shown.</p>	



UK Sales Direct: +44 (0)161 767 1122 | Export Sales Direct: +44 (0)161 767 1913  
Sample Requests: +44 (0)161 767 2551 | email: [info@polyflor.com](mailto:info@polyflor.com) | [www.polyflor.com](http://www.polyflor.com)

